Harlequin[®] torageTanks

RELIABLE CONTAINERS

Tank Dimensions:

Length: 3320mm Width: 2510mm

Overall Height: 3150mm Brimful Capacity: 11,000L Nominal Capacity: 10,450L

Net Weight: 640kg

Harlequin 10000ITE **Bunded Fuel Tank**



Harlequin ITE bunded oil tanks come equipped with a range of standard fittings, including an ultrasonic contents gauge and bottom outlet fitting kit – the complete solution for a fully compliant installation.

Standard Features:

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- Lockable equipment cabinet
- 2" BSP(M) offset fill point c/w non-return valve & lever ball valve
- Mechanical overfill prevention valve
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- Bottom outlet fitting kit (reducer, isolation valve, filter, 10mm oil line fitting)
- LRC overfill prevention probe
- **Bund monitor**
- Moulded-in handles for ease of lifting

Issued By:

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL150f Issue Date: August 2017 Issue: 01 Revision 00

Auth: JC