Harlequín[®] StorageTanks

RELIABLE CONTAINERS

Harlequin 3500ITE Bunded Fuel Tank

Tank Dimensions:

- Length: 2450mm
- Width: 1770mm
- Overall Height: 1890mm
- Brimful Capacity: 3471L
- Nominal Capacity: 3297L
- Net Weight: 275kg



Harlequin ITE bunded oil tanks come equipped with a range of standard fittings, including an ultrasonic contents gauge and bottom outlet fitting kit – the complete solution for a fully compliant installation.

Standard Features:

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 2" BSP(M) offset fill point with non-return valve
- Overfill prevention valve
- 4" lockable inspection cap
- Ultrasonic contents gauge with remote display
- Bottom outlet fitting kit (reducer, isolation valve, filter, 10mm oil line fitting)
- LRC overfill prevention probe
- Bund monitor
- Inner tank vent
- Galvanised steel lifting eyes for ease of handling

Issued By:

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL148b Issue: 01 Revision 02