

# KJN SERVICES LTD

## PRODUCT DATA SHEET

### RGHK5 MEWP Restraint Kit

Accredited to:	EN 361 & EN 354
Consists of:	RGH2 Front and Rear D Harness RGL12 Adjustable Restraint Lanyard 1.5m with 2 x RGK1 karabiners



The RGL12 is a single leg adjustable webbing restraint lanyard and acts as a leash for an operative working at height.

The adaptability of the product ensures that the correct length can be selected for the task in hand.

It is important to understand the principles of “fall-restraint” as the RGL12 can only be used for fall-restraint, as there is no shock absorption built into the system.

If there is any possibility of an operative stepping/falling over an exposed edge, or falling through a fragile surface, a fall arrest product should be used. The 37kN webbing used in the manufacture provides greater strength compared to other webbing and systems. The RGL12 should never be used to extend another fall arrest product.

Accredited to:	EN 354:2010
Material:	26mm water repellent polyester
Fittings:	Steel adjuster only. Supplied without connectors unless stated otherwise.
Lengths:	0.63m - 1m 0.89m - 1.5m 1.13m - 2m

The RGH2 harness is the 'workhorse' of the industry. The harness is fitted with a rear D attachment and a chest-mounted front D.

- It has the added feature of the front D ring to extend its working capability.
- Using the front D, the harness can be fitted with a rope and grab system (RGA12) for vertical fall protection when an operative is making repeated ascents.
- Can also be used when restraint is needed in either the vertical or horizontal plane.
- A variety of other devices can be used with the front D ring, but check for suitability.
- The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring.

Accredited to:	EN 361: 2002
Web material:	45mm water repellent polyester
Fittings:	High tensile steel alloy
Weight:	1.15kg
Features:	Front and rear attachment points Fully adjustable Rip stitch indicators
Sizes:	Small, Standard, Large and X-Large