

Diamond drilling tool

DD 130

The automatic choice



3

Applications

- For through holes up to 152 mm diameter in concrete with rig (8 - 62 mm hand-held) and 162 mm in masonry
- Wet drilling in concrete with drillstand / up to 152 mm, wet drilling in concrete hand-held / up to 62 mm, dry drilling in masonry hand-held / up to 162 mm, anchor holes (starter bars, mechanical anchors, adhesive anchors)
- Test cores, plumbing penetrations (waste, water), heating penetrations (air-conditioning, heating), electrical penetrations, electrical socket cutting, telecom penetrations, railings (stairs, balconies)
- Penetrations in brittle materials, in inhabited buildings, close to surface edges
- Ventilation penetrations, road and signage applications
- Drilling test cores

Advantages

- **Versatile** - Drills quickly and neatly in reinforced concrete, natural stone, masonry and asphalt and is designed for both wet and dry coring without modification
- **Simple** - Mobile and efficient: can be set-up and operated easily by a single person
- **Powerful** - High-performance 1600 W motor with plenty of power in reserve
- **Flexible** - Three gears for optimum power transmission and to suit the core bit diameter and material

Technical data

	DD 130
Rated current	16 A
Rated voltage	110 V
Speed 1 (no load)	780 rpm
Speed 2 (no load)	1400 rpm
Opt. drilling range - dry	16 mm - 132 mm
Opt. drilling range - wet hand held	16 mm - 112 mm
Weight in accordance with EPTA-Procedure 01/2003	7.3 kg

HILTI	up to 2 Years
LIFETIME SERVICE	NO COSTS
Lifetime	Lifetime
REPAIR COST LIMIT	MANUFACTURER'S WARRANTY

HILTI

FLEET MANAGEMENT



Ordering

Order description	Package Contents	Item number
Diamond coring tool DD 130 M 110v	Supplied in an impact resistant plastic tool case.	00372452



For DD-BI core bits see pages 161 - 167
 For VC Vacuum cleaners see page 198