

STRIPPING MACHINES

MS 230 Multistripper

The MS 230 multistripper has been developed to satisfy the requirements of removing floor coverings from smaller projects and confined areas.

This compact easy to operate machine offers the user a solution for commercial and domestic applications. Forward motion is achieved by manual effort made easier by the adjustable handle to suit different body heights. All components are manufactured from the highest grade materials ensuring strength and reliability.



Specifications		
Type	MS 230 Electric 110v	MS 230 Electric 220v
Part Number	MS 230-1	MS 230-2
Power Output	2.0hp	2.0hp
Voltage	110	220
Cycles	50hz	50hz
Machine Dimensions mm		
Length	685	685
Width	380	380
Height	787	787
Weight	45kg	45kg
Working width mm	230	230
Engine/Motor rpm	1400	1400

Features


- Fully adjustable chassis to adjust blade angle
- Large diameter wheels for excellent mobility and stability
- Simple clamp arrangement for quick and easy blade change
- Optimum weight distribution to ensure high work rate
- Handle height adjustable for operator control

Applications

- The removal of sheet vinyl, linoleum, cork, bonded carpet
- Woodblock, tiles, debonded membranes, sports surfaces
- Failed latex
- Build-up of excess materials in production areas
- Mortar/Plaster droppings from concrete floors in new build

Accessories	Part No.	Description
MS 230	C301	Std Blade

Electrical Requirements						
Machine	Volts	Plug Size	Cable Size mm	Max Cable Length	Transformer	Generator
MS 230-1	110	16A 3 Pin	2.5 3 Core	30 metres	3 kva	5 kva
MS 230-2	220	16A 3 pin	2.5 3 Core	30 metres	-	5 kva



Blade - C301