

TITAN FUELMASTER+ FUEL STORAGE AND DISPENSING TANK 1225-9000 LITRES

The Kingspan Titan FuelMaster+ range of fuel and diesel storage tanks is specifically designed for fuel dispensing and fuel protection and now allows you to monitor your tanks remotely giving you access to your fuel levels from anywhere.



SPECIFICATIONS

ALL TANKS OFFER THE FOLLOWING SPECIFICATION:

Guarantee Period - 10 years on tanks (1 year on components)

Fuel type - Agricultural Fuel Oil (Class 2A) and Gas/Oil/Diesel (Class D) and Diesel Fuel in accordance with BS EN590

Equipment options - Automatic Nozzle, 10m Hose Reel, 10 Micron Partile Filter, Tank Monitoring System

Product type	Oil level monitor	Capacity Ltr/Gal	Length (mm)	Width (mm)	Height (mm)	OFCERT N.	Pump options	Overfill prevention
1225	Clock gauge as standard	1225/270	2050	900	1970	Pending	3	SpillStop device as standard
1300	Clock gauge as standard	1300/285	1920	1230	1785	0642090326	Rotary, 12 Volt, 110 Volt, 230 Volt	SpillStop device as standard
2500	Clock gauge as standard	2500/550	2460	1460	1860	0642069837		Spillstop device

3500	Watchman3500/7552850 Anywhere Remote Oil Tank Monitoring	2200	1960	06420306301		Spillstop device as standard
4000	Watchman4000/8803900 Anywhere Remote Oil Tank Monitoring	1150	2340	Pending	3	Spillstop device as standard
5000	Watchman5000/11002850 Anywhere Remote Oil Tank Monitoring	2250	2350	0642060236		Spillstop device as standard
9000	Function 9000/1980280 in Tank Monitoring System	2450	2950	Pending	3	Spillstop device

OVERVIEW

BENEFITS

Secure fuel storage and efficient dispensing

Access oil levels from anywhere

Complete control over your fuel levels - giving you peace of mind

Remote Monitor comes with first 12 months free subscription - affordable annual subscription thereafter

Regulation Compliance: The Control of Pollution Regulations and comparable requirements across the UK and Ireland



OFCERT approved and manufactured to ISO standards for your complete peace of mind

FEATURES

Watchman Anywhere Remote Tank Monitoring comes as standard on capacities: 3500, 4000, 5000 and 9000 litres**

Clock Gauge comes as standard on 1225, 1300 and 2500 litres

10 micron particle & water filter standard

SpillStop overflow prevention device fitted as standard.

Pump which dispenses at 56 litres per minute as standard.

Pump options: Rotary, 12 Volt, 110 Volt, 230 Volt

Fitted light inside dispensing cabinet (230V version only).

Suitable for the following fuel types: Agricultural Fuel Oil (Class 2A) and Gas/Oil/Diesel (Class D) and Diesel Fuel in accordance with BSEN590

*Available on capacities: 3500, 4000, 5000 and 9000 litres

**In order to view the levels of the tank you must activate the unit by registering online via

www.watchmananywhere.com
