

# JollyMAX S

**ELECTRICAL TILE CUTTER  
WITH SLIDING CARRIAGE**

## Technical features

	JOLLY MAX S 230 art. 880S	JOLLY MAX S 300 art. 040S
Diamond disk:	ø 230 c/c standard	ø 300 TURBO standard
Engine:	Single phase 230V-50Hz 1,2Kw.	Single phase 230V-50Hz 2,3Kw.
Stand:	Included in the machine	Included in the machine
Max cutting length:	470 mm.	470 mm.
Max diagonal cut on size tile:	33 x 33 cm.	33 x 33 cm.
Max cutting thickness:	40 mm.	80 mm.
Max 45° angle cut on size tile:	40 x 40 cm.	40 x 40 cm.
Packing:	800 x 650 x 320 mm.	840 x 730 x 400 mm.
Weight:	32 kg.	43 kg.

# JollyMAX S

**ELECTRICAL TILE CUTTER  
WITH SLIDING CARRIAGE**



Art. 880S

## APPLICATIONS

**Electrical tile cutter for straight and 45° angle cuts on ceramic tiles, single fired tiles, gres, marble.**



DEALER



Zona Ind. 2 - Via Cavatorta, 6/1  
I-48010 COTIGNOLA (Ra) ITALY  
Tel. +39 0545 40696 - Fax +39 0545 41724  
www.nuova-battipav.com  
E-mail: nuova-battipav@nuova-battipav.com

# JollyMAX S 230

230V	1,2 Kw	Ø 230 c/c	40 mm	470 mm	•	32 Kg



# JollyMAX S

ELECTRICAL TILE CUTTER  
WITH SLIDING CARRIAGE

## Technical advantages

### CUT:

*Precise, safe and fast pushing on the sliding carriage.*

### CARRIAGE:

*Slide on chromed bars and on teflon guide having high resistance and long life.*

### SLIDING:

*On 3 pulleys mounted on ball-bearings.*



Direct reading of the cutting measure.



Direct reading of the cutting measure on diagonal.



Quick sliding without any lubrication necessity.



Easy to clean and to carriage.

# JollyMAX S 300

230V	2,3 Kw	Ø 300 turbo	80 mm	470 mm	•	43 Kg

