Edge Sander

Model HT7 Disc

Product Number 07003 (220/250V)

07004 (110/120V)

Power Supply 220/240V 50/60Hz

110/120V 50/60Hz

Off Load Current 220/250V-5A

110/120V=8A

Average Load Current 220/250V=8A

110/120V=15A

Noise 100 dB @ 3'3"

Vibration 2.71 m/s $\tilde{A}^-\hat{A}$ ¿ \hat{A} ½ r.m.s.

Switch Bias Off, double pole with power on indicator light

Motor Continuous heavy duty AC/DC self cooling 4 brush

Motor RPM 13,500

Drum/Disc/Pad RPM Off Load 3300

Sanding Drum/Disc/Pad 7" dia. metal backed and rubber bonded

Drive Hardened steel alloy pinion and large diameter phosphor bronze drive

gear

Dust Pickup

Seated oversize alloy vacuum fan with adjustable dust pan, disposable

paper dust or cloth bag

Moving Parts Sealed for life ball bearings

Guards High impact injection molded ABS

Abrasive 7" dia. x 7/8" dia. center hole recommended range P16 to P120 grit

fiber or paper back

Power Cable 23' non-marking outer insulation

Dimensions (w x d x h) 10/8" x 19.9" x 12.8"

Weight Net 36.2lbs